

## WIRELESS DESKTOP PRINTER



### GSS-Label-PTR-D-Wireless

The GSS-LABEL-PTR-D-Wireless desktop printer offers built-in WiFi that allows you to place the printer where it best maximizes efficiency for your shop floor, instead of being limited to an inconvenient location. It's a high-performance printer designed for space-constrained environments and features a compact footprint and an easy-to-use clamshell design for quick media changes.

PERFORMANCE		PHYSICAL CHARACTERISTICS CONTINUED	
Resolution	203 DPI (8 dots/mm)	Media Core Diameter	25.4 ~ 38.1 mm (1" ~ 1.5")
Memory	128 MB Flash memory, 128 MB SDRAM (microSD card reader for Flash memory expansion, up to 32 GB)	Label Length	3 ~ 25,400 mm (0.1" ~ 1,000")
Printing Method	Thermal Transfer & Direct Thermal	Font & Barcode Rotation	0, 90, 180, 270 degree
Processor	32-bit RISC CPU	Sensors	Transmissive gap sensor, Black mark reflective sensor (position adjustable), Ribbon encode sensor, Head open sensor
Max. Print Speed	203 mm (8") / second	Internal Fonts	8 Alpha-numeric bitmap fonts, Monotype Image® true type font engine with on CG Triumvirate Bold Condensed scalable font
Max. Print Width	108 mm (4.25")	1D Barcode	Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codebar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS
Max. Print Length	25,400 mm (1,000")	2D Barcode	TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF-417, GS1 DataBar (RSS barcode)
Enclosure	Clamshell with double-walled plastic	Environmental Condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Interface	Wireless a/b/g/n, USB 2.0, RS-232, Internal Ethernet (10/100 Mbps)	Safety Regulation	FCC Class B, CE Clas B, RCM, UL, cUL, TÜV/Safety, CCC, BIS, EAC, ENERGY STAR®
Display	3.5 Inch TFT display	<b>WARRANTY</b>	
<b>PHYSICAL CHARACTERISTICS</b>		Warranty	3 Year standard comprehensive warranty
Physical Dimension	Dimensions: 8.90 in. (W) x 7.80 in. (H) x 13.07 in. (D) / 226 mm (W) x 198 mm (H) x 332 mm (D)		
Weight	8.27 lbs. (3.75 kg)		
Label Roll Capacity	127 mm (5") OD		
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside)		
Ribbon Width	40 mm ~ 110 mm (1.6" ~ 4.3")		
Media Width	19 ~ 112 mm (0.75" ~ 4.4")		
Media Thickness	0.055 ~ 0.254 mm (2.17 ~ 10 mil)		

