

## DESKTOP LABEL PRINTER / GSS-LABEL-PTR-D



### GSS-LABEL-PTR-D

GSS-LABEL-PTR-D desktop printers are built for space- constrained desktop environments, and feature a compact footprint and an easy-to-use clamshell design for quick media changes. The printer is ideal for business use, compliance labeling, asset and inventory tracking and medical applications.

PERFORMANCE		PHYSICAL CHARACTERISTICS CON'T	
Resolution	8 dots/mm (203 DPI)	Media core diameter	25.4 ~ 38.1mm (1"~ 1.5")
Memory	4 MB Flash memory, 8 MB SDRAM	Label length	10 ~ 2,286 mm (0.39"~ 90")
Operation Switch, Button, LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)	Font and barcode rotation	0, 90, 180, 270 degree
Power	External universal switching power supply, Input: AC 100-240V, 2.5A, 50-60 Hz, Output: DC 24V, 2.5A, 60W	Sensors	Gap transmissive sensor, Black mark reflective sensor (position adjustable), Head open sensor, Ribbon end sensor
Printing method	Thermal Transfer & Direct Thermal	Internal fonts	8 alpha-numeric bitmap fonts, Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Max. print speed	102 mm (4")/second	Bar code	1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, GS1 DataBar, Logmars, Code 11
Max. print width	108 mm (4.25")	2D bar code	PDF-417, Maxicode, DataMatrix, QR code, Aztech
Max. print length	2,286 mm (90")	Environmental Condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Enclosure	Double-walled plastic	Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC
PHYSICAL CHARACTERISTICS		WARRANTY	
Physical Dimension	202mm (W) x 173 mm (H) x 258 mm (D) 7.95" (W) x 6.81" (H) x 10.16" (D)	Warranty	3 YEAR STANDARD COMPREHENSIVE WARRANTY
Weight	2.3 kg (5.07 lbs)		
Label roll capacity	127 mm (5") OD		
Ribbon	110 m long, max. OD 40 mm, 0.5" core (ink coated outside)		
Ribbon width	40 mm ~ 110 mm (1.57"~ 4.33")		
Media width	20 ~ 112 mm (0.79"~ 4.4")		
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)		

1. Minimum 13 hours under WLAN and laser scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, Bluetooth® off / IEEE 802.11 a/b/g/n on. The test is based on one broadcasting packet per second.